



laundry equipment

# Professional Washer Extractor Professional Dryer

**SC65** 

DAM6



#### FEATURES WASHER EXTRACTORS

- Stainless steel look
- Stainless steel drum and tub
- Easy to use timer mop and medical programmes
- Soap hopper at the front
- Matching dryer available space saving when placed on top

### **OPTIONS WASHER EXTRACTORS**

- External coin meter
- Drain valve
- Liquid soap pumps
- Marine voltages available

#### **FEATURES DRYERS**

- Stainless steel look
- Stainless steel drum and tub
- Large door opening (Ø45cm)

## **OPTIONS DRYERS**

- External coin meter
- Condens unit (DAMC)
- Marine voltages available
- Heat pump heating (DAM6HP)









| 60                    |  |  |  |
|-----------------------|--|--|--|
| Ø480                  |  |  |  |
| 1400                  |  |  |  |
| 530                   |  |  |  |
| 1×230-400V 50Hz       |  |  |  |
| 3×400V 50Hz           |  |  |  |
| 1x220Vx60Hz           |  |  |  |
| 3x440Vx60Hz           |  |  |  |
| 3,2                   |  |  |  |
| 230V-16A/400V-10A     |  |  |  |
| 3/4"                  |  |  |  |
| Pump Standard         |  |  |  |
| drain valve available |  |  |  |
|                       |  |  |  |
| 850×595×585           |  |  |  |
|                       |  |  |  |
|                       |  |  |  |
| 77                    |  |  |  |
| 73                    |  |  |  |
|                       |  |  |  |
| 0,53                  |  |  |  |
|                       |  |  |  |
| 915×610×660           |  |  |  |
|                       |  |  |  |
|                       |  |  |  |

**SC65** 

6,5

kg

mm

rpm

kW

inch

mm

kg

kg

 $\,m^3$ 

mm

| TYPE              |                | DAM6 C      | DAM6   | DAM6 HP   |
|-------------------|----------------|-------------|--------|-----------|
|                   |                | condense    | vented | heat pump |
| CAPACITY          | kg             | 6,5         |        |           |
| DRUM VOLUME       | 1              | 112         |        |           |
| DIMENSIONS DRUM   | mm             | Ø571×476    |        |           |
| ELECTRICAL        |                | 1×230V 50Hz |        |           |
| CONNECTION        |                | 3×400V 50Hz |        |           |
|                   |                | 1×220V×60Hz |        |           |
|                   |                | 3x440Vx60Hz |        |           |
| ELECTRICAL        | kw             | 2,5         | 3      | 1,3       |
| HEATING           |                | 0001/1/1    |        |           |
| CIRCUIT BREAKER   |                | 230V-16A    |        |           |
|                   |                | 400V-10A    |        |           |
| AIRFLOW           | m³/h           | 123         | 245    | internal  |
| AIR EVACUATION    | mm             | -           | 100    | -         |
| DIMENSIONS        |                | 850×595×585 |        |           |
| H×W×D             | mm             | 050/575/505 |        |           |
| TRANSPORT DATA    |                |             |        |           |
| Gross weight      |                |             |        |           |
| Cardboard packing | kg             | 50          | 45     | 56        |
| Net weight        | kg             | 47          | 39     | 52        |
| Volume (packed)   |                |             |        | '         |
| Cardboard packing | m <sup>3</sup> |             | 0,53   |           |
| Cardboard packing |                |             |        |           |
| H×W×D             | mm             | 915×610×660 |        |           |



**TYPE** 

CAPACITY

**G-FACTOR** 

**ELECTRICAL** 

CONNECTION

DRUM VOLUME

DRUM DIAMETER

EXTRACTION SPEED

**ELECTRICAL HEATING** 

**CIRCUIT BREAKER** WATER CONNECTION

DRAIN

H×W×D

Net weight

HxWxD

Volume (packed) Cardboard packing

Cardboard packing

DIMENSIONS

TRANSPORT DATA Gross weight Cardboard packing



